

RTC - RTD

Modelo Model	Potência Power (HP)	Pressão Working pressure (Bar)	Caudal Air ranger S/ISO1217 (l/min)	Nível acústico Noise level (dB)	Lig. Fittings (Gas)	Peso Weight (Kg)	Dimensões Dimensions (mm)
Série RTC							
RTC 30/8	30	8	3930	68	1 1/4"	680	1100x1390x1545
RTC 30/10	30	10	3270	68	1 1/4"	680	1100x1390x1545
RTC 30/13	30	13	2470	68	1 1/4"	680	1100x1390x1545
RTC 40/8	40	8	4900	69	1 1/4"	695	1100x1390x1545
RTC 40/10	40	10	4310	69	1 1/4"	695	1100x1390x1545
RTC 40/13	40	13	3460	69	1 1/4"	695	1100x1390x1545
RTC 50/8	50	8	6080	70	1 1/4"	715	1100x1390x1545
RTC 50/10	50	10	5540	70	1 1/4"	715	1100x1390x1545
RTC 50/13	50	13	4250	70	1 1/4"	715	1100x1390x1545
RTC 60/8	60	8	7790	71	1 1/2"	790	1100x1390x1805
RTC 60/10	60	10	6810	71	1 1/2"	790	1100x1390x1805
RTC 60/13	60	13	5710	71	1 1/2"	790	1100x1390x1805
RTC 75/8	75	8	8630	71	1 1/2"	810	1100x1390x1805
RTC 75/10	75	10	7800	71	1 1/2"	810	1100x1390x1805
RTC 75/13	75	13	6420	71	1 1/2"	810	1100x1390x1805
RTC 100/8	100	8	11340	74	1 1/2"	980	1100x1930x1175
RTC 100/10	100	10	10500	74	1 1/2"	980	1100x1930x1175
RTC 100/13	100	13	8715	73	1 1/2"	980	1100x1930x1175
Série RTD							
RTD 75/8	75	8	10180	69	1 1/2"	1075	1100x1930x1765
RTD 75/10	75	10	8850	69	1 1/2"	1075	1100x1930x1765
RTD 75/13	75	13	7150	69	1 1/2"	1075	1100x1930x1765
RTD 100/8	100	8	13880	69	1 1/2"	1125	1100x1930x1765
RTD 100/10	100	10	11860	69	1 1/2"	1125	1100x1930x1765
RTD 100/13	100	13	10480	69	1 1/2"	1125	1100x1930x1765
RTD 125/8	125	8	14980	70	1 1/2"	1175	1100x1930x1765
RTD 125/10	125	10	13020	70	1 1/2"	1175	1100x1930x1765
RTD 125/13	125	13	11340	70	1 1/2"	1175	1100x1930x1765

Caudais segundo a norma ISO 1217 e Cagi-Pneurop CPTC2 - According TO ISO 1217 and cagi pneurop CPTC2

Alimentação padrão 400 volt / 50 Hz / 3 Fases - Voltage 400 / 50HZ / 3 phases

